



Examples of ILC Cryogenic Systems Cost Optimization

T. Peterson
28 September 2007



Possibility for Cost Optimization

- Cryomodule / cryogenic system cost trade-off studies
- Costs of the cryomodules per meter are much larger than the costs of the cryogenic system per meter
- Optimization studies for capital and operating costs should consider tradeoffs of cryomodule complexity with heat loads
 - **For example, thermal shields, thermal intercepts, and MLI can perhaps be simplified for efficient production**
 - **At a minimum, the 5 Kelvin thermal shield bridges at cryomodule interconnects can probably be eliminated**




Two examples

- Remove the entire 5 K thermal shield
 - **Retain the 5 K - 8 K piping and thermal intercepts**
- Remove only the 5 K thermal shield bridge at interconnects



Type 4 cryomodule





Heat loads scaled from TESLA TDR

Cryomodule	TESLA	ILC 9-8-9
E, [MV/m]	23.4	31.5
Q	1.E+10	1.E+10
Rep rate, [Hz]	5	5
Number of Cavities	12	8.667
Fill time [μsec]	420	597
Beam pulse [μsec]	950	969
Number of bunches	2820	2670
Particles per bunch [1e10]	2	2.04
Gfac		2.09
Pfac		1.54
Bfac		0.99
Cfac		0.95

ILC 8-8-8 and 9-8-9 refers to the number of cavities in
G

avg number of cavities per module

Tf

Tb

Nb

Qb

Stored Energy Factor = $G^2 \cdot (Tb + 1.1 \cdot Tf)$

Input Power Factor = $G \cdot (Tb + 2 \cdot Tf) \cdot Cfac$

Bunch Factor = $Nb \cdot Qb^2$

Beam Current Factor = $Qb \cdot Nb / Tb$



Module predicted heat loads -- 5K

With removal of 5 K thermal shield, radiative load goes down to 2 K level

	TESLA		ILC 9-8-9	
	5K		5K	
Radiation	1.95		1.41	
Supports	2.40		2.40	
Input coupler	2.05	1.19	1.48	1.32
HOM coupler (cables)	0.40	2.66	0.29	1.82
HOM absorber	3.13	0.77	3.13	0.76
Current leads			0.47	0.47
Diagnostic cable	1.39	-	1.39	-
Scales as Pfac		1.19		1.32
Independent of G,Tf	11.32	3.43	10.56	3.04
Static, dynamic sum	11.32	4.62	10.56	4.37
5K Sum [W]	15.9		14.9	

- Static load scaled by number of cavities
- Assume independent of number of cavities
- Static load scaled by number of cavities, dynamic by Pfac also
- Static and dynamic load scaled by number of cavities, dynamic by Cfac also
- Dynamic load scaled by Bfac
- Weigh by a factor of 1/3 since only 1 in 3 modules have quads**
- Assume independent of number of cavities

Total for 9-8-9 RF unit below
44.80

Retain the 5 K - 8 K helium circuit for thermal intercepts



Module predicted heat loads -- 2K

TESLA ILC 9-8-9

Additional 1.41 W static heat

Temperature Level	2K		2K	
RF load		4.95	1.41	7.46
Supports	0.60		0.60	-
Input coupler	0.76	0.14	0.55	0.16
HOM coupler (cables)	0.01	0.27	0.01	0.18
HOM absorber	0.14	0.02	0.14	0.01
Beam tube bellows		0.24		0.36
Current leads	0.04		0.28	0.28
HOM to structure		1.68		1.20
Coax cable (4)	0.05		0.05	
Instrumentation taps	0.07		0.07	
Scales as Gfac		5.19		7.83
Scales as Pfac		0.14		0.16
Independent of G,Tf	1.67	1.97	3.11	1.68
Static, dynamic sum	1.67	7.30	3.11	9.66
2K Sum [W]		9.0		12.8

Dynamic load scaled by the number of cavities and Gfac
 Taking thermal radiation to 2 K, no 5 K shield
 Assume independent of number of cavities
 Static load scaled by number of cavities, dynamic by Pfac also
 Static and dynamic load scaled by number of cavities, dynamic by Cfac also
 Dynamic load scaled by Bfac
 Dynamic load scaled by the number of cavities and Gfac
 Weigh by a factor of 1/3 since only 1 in 3 modules have quads**
 Static load scaled by the number of cavities, dynamic by Bfac also
 Assume indepent of number of cavities
 Assume indepent of number of cavities

Total for 9-8-9 RF unit below
 38.30

Note: implied is a pessimistic assumption that view factor of 2 K objects is as large as 5 K thermal shield



Module predicted heat loads -- 40K

No significant change

TESLA ILC 9-8-9

	40K		40K	
Radiation	44.99		32.49	
Supports	6.00		6.00	
Input coupler	21.48	59.40	15.51	66.08
HOM coupler (cables)	2.55	13.22	1.84	9.04
HOM absorber	(3.27)	15.27	(3.27)	15.04
Current leads			4.13	4.13
Diagnostic cable	2.48		2.48	
Scales as Pfac		59.40		66.08
Independent of G,Tf	74.23	28.49	59.19	28.22
Static, dynamic sum	74.23	87.89	59.19	94.30
40K Sum [W]	162.1		153.5	

Static load scaled by number of cavities
 Assume independent of number of cavities
 Static load scaled by number of cavities, dynamic by Pfac also
 Static and dynamic load scaled by number of cavities, dynamic by Cfac also
 Dynamic load scaled by Bfac
 Weigh by a factor of 1/3 since only 1 in 3 modules have quads**
 Assume independent of number of cavities

Total for 9-8-9 RF unit below
 460.46



Cryogenic unit parameters

With 5 K thermal shield

		40 K to 80 K	5 K to 8 K	2 K
Predicted module static heat load	(W/module)	59.19	10.56	1.70
Predicted module dynamic heat load	(W/module)	94.30	4.37	9.66
Number of modules per cryo unit (8-cavity modules)		192.00	192.00	192.00
Non-module heat load per cryo unit	(kW)	1.00	0.20	0.20
Total predicted heat per cryogenic unit	(kW)	30.47	3.07	2.38
Heat uncertainty factor on static heat (F _{us})		1.10	1.10	1.10
Heat uncertainty factor on dynamic heat (F _{ud})		1.10	1.10	1.10
Efficiency (fraction Carnot)		0.28	0.24	0.22
Efficiency in Watts/Watt	(W/W)	16.45	197.94	702.98
Overcapacity factor (F _o)		1.40	1.40	1.40
Overall net cryogenic capacity multiplier		1.54	1.54	1.54
Heat load per cryogenic unit including F _{us} , F _{ud} , and F _o	(kW)	46.92	4.72	3.67
Installed power	(kW)	771.72	934.91	2577.65
Installed 4.5 K equiv	(kW)	3.53	4.27	11.78
Percent of total power at each level		18.0%	21.8%	60.2%
Total operating power for one cryo unit based on predicted heat (MW)			3.34	
Total installed power for one cryo unit (MW)			4.28	
Total installed 4.5 K equivalent power for one cryo unit (kW)			19.57	



Cryogenic unit parameters

No 5 K thermal shield

		40 K to 80 K	5 K to 8 K	2 K
Predicted module static heat load	(W/module)	59.19	9.16	3.11
Predicted module dynamic heat load	(W/module)	94.30	4.37	9.66
Number of modules per cryo unit (8-cavity modules)		192.00	192.00	192.00
Non-module heat load per cryo unit	(kW)	1.00	0.20	0.20
Total predicted heat per cryogenic unit	(kW)	30.47	2.80	2.65
Heat uncertainty factor on static heat (F _{us})		1.10	1.10	1.10
Heat uncertainty factor on dynamic heat (F _{ud})		1.10	1.10	1.10
Efficiency (fraction Carnot)		0.28	0.24	0.22
Efficiency in Watts/Watt	(W/W)	16.45	197.94	702.98
Overcapacity factor (F _o)		1.40	1.40	1.40
Overall net cryogenic capacity multiplier		1.54	1.54	1.54
Heat load per cryogenic unit including F _{us} , F _{ud} , and F _o	(kW)	46.92	4.31	4.08
Installed power	(kW)	771.72	852.48	2870.38
Installed 4.5 K equiv	(kW)	3.53	3.89	13.11
Percent of total power at each level		17.2%	19.0%	63.9%
Total operating power for one cryo unit based on predicted heat (MW)			3.50	
Total installed power for one cryo unit (MW)			4.49	
Total installed 4.5 K equivalent power for one cryo unit (kW)			20.54	



Cryogenic system cost

- Cost impact is calculated for cryoplants and their installation but not for distribution system
 - **Installed plant power increases from 4.28 to 4.49 MW for each of the large cryoplants**
 - **Assume capital cost increases by installed power $^{0.6}$**
 - **\$7.59 M total cryogenic plants capital cost increase**
 - **1815 standard 1.3 GHz cryomodules including sources (not including multi-magnet cryomodules)**
- Cryosystem additional M&S is \$4200 per cryomodule
- Cryogenic plant operating power
 - **Increases from 3.34 MW to 3.50 MW for each of the 10 large plants**
 - **Total of 1.6 MW added for ILC cryogenic system**
- Added operating cost at \$0.10/kW-hr is \$1.38M/yr or \$770 per cryomodule per year



5 K thermal shield cost data

- LHC
 - **Thermal shield for dipole cryostats was \$550/meter (M&S only)**
 - A bit simpler than ILC cryomodule 5 K and 40 K thermal shields since not so many feedthroughs
 - Input couplers are a complication for ILC
 - MLI not included
 - **MLI cost is about \$130/m**
 - **So with MLI M&S is about \$680/m or \$8600 per cryomodule**



5 K thermal shield cost estimates

- Industrial cost estimate
 - **M&S estimate for 5 K shield including MLI is \$4000**
 - **Installation labor is estimated at \$1700**
- Fermilab cost estimate
 - **M&S estimate for 5 K shield including MLI is \$5900 based on US LHC costs**
- Shield cost conclusion
 - **Average the two estimates and LHC costs**
 - **Total cost is \$6200 M&S + \$1700 labor = \$7900 per cryomodule**



Result of preliminary analysis

- Removal of 5 K thermal shield results in M&S savings of \$7900 (shield) - \$4200 (cryo) = \$3700 per cryomodule
- Operating costs increase by about \$770 per cryomodule per year
 - **Payback for 5 K shield is about 5 years**
- It may end up close to “break-even” or difficult to identify a definite cost advantage
 - **In general, with several alternatives which satisfy system requirements and show no clear cost difference, the “tie-breaking” criterion should be to take the simpler approach**



Next steps -- refine analysis

- Investigate thermal shield cost
 - **LHC experience and estimates differ**
 - **Assembly labor also uncertain**
 - **Secondary benefits of simplification not counted**
- Investigate real addition to 2 K heat
 - **Assumed same view factor to 2 K system as to 5 K shield, which is pessimistic**
- Consider alternative warm thermal shield temperatures with absence of 5 K shield



5 K thermal shield bridge removal

- Removal of the 5 K thermal shield bridge from the cryomodule interconnects should provide net gain
 - Length is ~800 mm, and thermal impact scales with shield length removed = $0.8/12.65$
 - Impact on cryoplant M&S is no more than $0.063 \times \$4200 = \270 added cryogenic system M&S per cryomodule
 - Less since little at 2 K in interconnect
 - Impact on operating costs is $0.063 \times \$770 = \50 per cryomodule per year
- Shield bridge interferes with pipe interconnect bellows and is labor-intensive to install, so cost is more than the per meter shield cost
 - Cost more than \$500 per cryomodule
- Result is net savings for leaving out the 5 K thermal shield bridge at interconnects even after 5 years



Cryomodule/cryogenics optimization is a Work Package

- Work package #9 in Cryogenic Systems list
 - **High priority**
 - **A joint task with cryomodules**
 - **Norihito Ohuchi responsible for KEK effort on this topic**
 - KEK may do tests at STF regarding the 5 K thermal shield in addition to analysis
 - **Vittorio Parma responsible for CERN effort**
 - Will consist of input from LHC experience
 - One input already -- LHC eliminated their 5 K thermal shield after a similar study
 - **Tom Peterson will coordinate Fermilab effort for this work package**