


The field cage for the Large TPC-Prototype



DESY FLC TPC Group

Ties Behnke, Klaus Dehmelt, Ralf Diener, Lea Hallermann, Peter Schade

EUDET Setup



BALLOON-BORNE EXPERIMENT WITH A SUPERCONDUCTION
MAGNET SPECTROMETER, Akira Yamamoto, KEK, 01.12.94

- infrastructure for TPC R&D, available for many researcher groups
 - ↪ PCMAG was installed in the e^- test beam in December 2006
 - ↪ Large TPC-Prototyp: 60 cm long drift volume, 72 cm inner diameter


Requirements

- operation in the e^- test beam \rightarrow walls need to be as thin as possible (less than 2 % of a radiation length)
- homogeneity of the electric field $\Delta E/E < 10^{-4}$

Requirements

- operation in the e^- test beam \rightarrow walls need to be as thin as possible (less than 2% of a radiation length)
- homogeneity of the electric field $\Delta E/E < 10^{-4}$


\rightarrow composite materials




Requirements

- operation in the e^- test beam \rightarrow walls need to be as thin as possible (less than 2% of a radiation length)
- homogeneity of the electric field $\Delta E/E < 10^{-4}$

\rightarrow composite materials




\rightarrow electrostatic calculations




Requirements

- operation in the e^- test beam \rightarrow walls need to be as thin as possible (less than 2% of a radiation length)
- homogeneity of the electric field $\Delta E/E < 10^{-4}$

\rightarrow composite materials




\rightarrow electrostatic calculations




- field- and mirror-strips as inner layer
- parallelism of anode and cathode at $100 \mu\text{m}$ level


Field strip foil




- flexible circuit board 60 cm × 230 cm
 - ↳ combined from two 30 cm wide pieces
- SMD-resistors: 1 M Ω \pm 0.05 % sorted
 - ↳ foil equipped with 1 M Ω \pm 0.02 % resistors



Field strip foil





- flexible circuit board 60 cm × 230 cm
 - ↳ combined from two 30 cm wide pieces
- SMD-resistors: 1 MΩ ± 0.05 % sorted
 - ↳ foil equipped with 1 MΩ ± 0.02 % resistors




Sample pieces of the wall

- different possible cross sections of the investigated with sample pieces
 - ↳ high voltage tests up to 30 kV
 - no breakdown in 48 h
 - ↳ mechanical tests
 - 4-point bending tests
- final layout has 1.3 % of an radiation length





Radiation Length: 1.31% of X_0




Sample pieces of the wall

- different possible cross sections of the investigated with sample pieces
 - ↳ high voltage tests up to 30 kV
 - no breakdown in 48 h
 - ↳ mechanical tests
 - 4-point bending tests
- final layout has 1.3 % of an radiation length




Radiation Length: 1.31% of X_0



Production of the chamber on a mandrel


- field strip foil will be put as first layer
↳ mandrel has two slots



Production of the chamber on a mandrel


- field strip foil will be put as first layer
 ↳ mandrel has two slots

 Feldstreifen mit SMD Widerst.




Production of the chamber on a mandrel

- field strip foil will be put as first layer
 - ↳ mandrel has two slots
- in the following layers are laminated:
 - ↳ high voltage insulation 125 μm thick polyimid foil




Production of the chamber on a mandrel

- field strip foil will be put as first layer
 - ↳ mandrel has two slots
- in the following layers are laminated:
 - ↳ high voltage insulation 125 μm thick polyimid foil
 - ↳ inner GRP layer (300 μm thick)





Production of the chamber on a mandrel

- field strip foil will be put as first layer
 - ↳ mandrel has two slots
- in the following layers are laminated:
 - ↳ high voltage insulation 125 μm thick polyimid foil
 - ↳ inner GRP layer (300 μm thick)
 - ↳ aramid honeycomb and end flanges made of a hard foam





Production of the chamber on a mandrel

- field strip foil will be put as first layer
 - ↳ mandrel has two slots
- in the following layers are laminated:
 - ↳ high voltage insulation 125 μm thick polyimid foil
 - ↳ inner GRP layer (300 μm thick)
 - ↳ aramid honeycomb and end flanges made of a hard foam





Production of the chamber on a mandrel

- field strip foil will be put as first layer
 - ↳ mandrel has two slots
- in the following layers are laminated:
 - ↳ high voltage insulation 125 μm thick polyimid foil
 - ↳ inner GRP layer (300 μm thick)
 - ↳ aramid honeycomb and end flanges made of a hard foam
 - ↳ additional thin aramid layer





Production of the chamber on a mandrel

- field strip foil will be put as first layer
 - ↳ mandrel has two slots
- in the following layers are laminated:
 - ↳ high voltage insulation 125 μm thick polyimid foil
 - ↳ inner GRP layer (300 μm thick)
 - ↳ aramid honeycomb and end flanges made of a hard foam
 - ↳ additional thin aramid layer
 - ↳ outer GRP layer (300 μm thick)





Production of the chamber on a mandrel

- field strip foil will be put as first layer
 - ↳ mandrel has two slots
- in the following layers are laminated:
 - ↳ high voltage insulation 125 μm thick polyimid foil
 - ↳ inner GRP layer (300 μm thick)
 - ↳ aramid honeycomb and end flanges made of a hard foam
 - ↳ additional thin aramid layer
 - ↳ outer GRP layer (300 μm thick)
 - ↳ outer insulation (copper covered Kapton foil)



Production of the chamber on a mandrel

- field strip foil will be put as first layer
 - ↳ mandrel has two slots
- in the following layers are laminated:
 - ↳ high voltage insulation 125 μm thick polyimid foil
 - ↳ inner GRP layer (300 μm thick)
 - ↳ aramid honeycomb and end flanges made of a hard foam
 - ↳ additional thin aramid layer
 - ↳ outer GRP layer (300 μm thick)
 - ↳ outer insulation (copper covered Kapton foil)
- mandrel has an expansion slot
 - ↳ reduction of the diameter



Status of the construction




- mandrel made of aluminium
 - ↪ diameter: $\Delta d \approx 0.5 \text{ mm}$
 - ↪ position of slot corrected

Status of the construction




- mandrel made of aluminium
 - ↪ diameter: $\Delta d \approx 0.5 \text{ mm}$
 - ↪ position of slot corrected
- field strip foil mounted

Status of the construction




- mandrel made of aluminium
 - ↪ diameter: $\Delta d \approx 0.5 \text{ mm}$
 - ↪ position of slot corrected
- field strip foil mounted
 - ↪ remaining slot $< 0.5 \text{ mm}$
 - ↪ alignment worked well

Status of the construction




- mandrel made of aluminium
 - ↪ diameter: $\Delta d \approx 0.5 \text{ mm}$
 - ↪ position of slot corrected
- field strip foil mounted
 - ↪ remaining slot $< 0.5 \text{ mm}$
 - ↪ alignment worked well
- Kapton glued onto the foil
- first GRP layer attached

Status of the construction




- mandrel made of aluminium
 - ↪ diameter: $\Delta d \approx 0.5 \text{ mm}$
 - ↪ position of slot corrected
- field strip foil mounted
 - ↪ remaining slot $< 0.5 \text{ mm}$
 - ↪ alignment worked well
- Kapton glued onto the foil
- first GRP layer attached
 - ↪ air inclusions reduced by under pressure treatment

Status of the construction




- mandrel made of aluminium
 - ↪ diameter: $\Delta d \approx 0.5 \text{ mm}$
 - ↪ position of slot corrected
- field strip foil mounted
 - ↪ remaining slot $< 0.5 \text{ mm}$
 - ↪ alignment worked well
- Kapton glued onto the foil
- first GRP layer attached
 - ↪ air inclusions reduced by under pressure treatment
- epoxy is tempered at 60°C

Status of the construction



- mandrel made of aluminium
 - ↪ diameter: $\Delta d \approx 0.5 \text{ mm}$
 - ↪ position of slot corrected
- field strip foil mounted
 - ↪ remaining slot $< 0.5 \text{ mm}$
 - ↪ alignment worked well
- Kapton glued onto the foil
- first GRP layer attached
 - ↪ air inclusions reduced by under pressure treatment
- epoxy is tempered at 60°C
- flange machined and glued onto the GRP layer

Status of the construction




- mandrel made of aluminium
 - ↪ diameter: $\Delta d \approx 0.5 \text{ mm}$
 - ↪ position of slot corrected
- field strip foil mounted
 - ↪ remaining slot $< 0.5 \text{ mm}$
 - ↪ alignment worked well
- Kapton glued onto the foil
- first GRP layer attached
 - ↪ air inclusions reduced by under pressure treatment
- epoxy is tempered at 60°C
- flange machined and glued onto the GRP layer

- construction is expected to be finished this week
- field cage will be available at DESY end of June

Construction of a cathode


- cathode made of aluminium
 - ↳ electroplated with copper
 - ↳ a pattern can be machined into the surface
- will be mounted on an intermediate flange
- three adjustable screws carry the cathode plate
 - ↳ correct placement of cathode surface
 - ↳ adjustment of parallelism
- cathode plate ready, construction of intermediate flange soon



Conclusion



- field cage for a Large TPC-Prototype for the ILC as a part of an EUDET infrastructure
- construction of the chamber ongoing
- a first cathode is under preparation
- chamber available in June
 - ↳ HV-tests
 - ↳ gas tests
- a first anode plate is under construction at the university of Cornell
- measurements in the test beam starting in September

EUDET Setup



- infrastructure for TPC R&D, available for many researcher groups
 - ↪ PCMAG was installed in the e^- test beam in December 2006
 - ↪ Large TPC-Prototype: 60 cm long drift volume, 72 cm inner diameter
 - ↪ among others: studies for TPC-operation in inhomogeneous fields planned

Pull out tests of inserts



- force requested to compress the O-ring
 ↪ 1.2 kN per insert, with safety: 3.6 kN
- self made inserts

