



Accelerator / Beam Transport

John Carwardine

(From discussions with N. Golubeva, V. Balandin)






Experience with 3nC lattice during 9mA studies

- May 08
 - We were unable to get low-loss transport of 3nC bunches through the bypass line.
- September 08
 - Took less than a shift to get low-loss transport of 3nC bunches through the bypass
 - Largely attributed to careful setup of laser, gun and injector
 - Losses in BC3 were difficult to keep low.
- January 09
 - Low-loss transport of 3nC bunches achieved repeatedly over several shifts using same lattice as for 1nC. Only required injector matching and steering.
 - Loss at BC3 still a problem.



Bypass optics not well understood



N. Golubeva (16.6.08)

Steerer V10ACC7 (currents 0.07 and 0.06 amperes, 30 measurements for re

Dump line lattice elements





Issues/concerns for full 9mA run

- Highly dependent on a good injector setup for low-loss transport
- Losses in BC3 still an issue
- Bypass optics not well understood

- ACC1 cavities need to be carefully matched in phase
 - **Differences in relative phases will increase energy spread**
- Amplification of energy jitter through bunch compressors
 - **Consider running with BC2 off...?**

- Currently cannot measure the beam trajectory in the dump line
 - **Install new bpms (cf talks by K. Wittenburg, M. Schmitz)**
 - **Screen at 9DUMP: survey position relative to beam pipe**
- Align Q9DUMP and Q10DUMP to minimize kicks
- Only one steerer in the dump line (cf M. Schmitz talk)