

Low E e- driven e⁺ source

as a summary of e⁺ meeting on 09/01/13.

Masao KURIKI (Hiroshima/KEK)

A horizontal dotted line in a light green color is located at the bottom of the slide.



Low E e- driven e+ source

- ▶ The low E e- driven e+ source has been proposed by MK at ILC08. It was updated by considering DR acceptance.
- ▶ Critical investigation was made by W. Liu and W. Gai (ANL group).
- ▶ Two studies are compared.

Positron Yield study (MK)

- ▶ Positron generation is simulated by NRC-EGS4 with various electron energy (0.25 – 6.0 GeV) as a function of the target thickness (0.5 – 8.0 X_0).
- ▶ Beam spot : 2.5mm radius (rms)
- ▶ Capture optics: AMD ($B_0=7.0\text{T}$, $B_s=0.5\text{T}$, $L=220\text{mm}$, $\mu=60.8\text{ 1/m}$)
- ▶ Positron acceptance is qualified by an analytical method .
- ▶ DR acceptance is accounted. The real yield is 87% of the yield at AMD + capture RF.
- ▶ No enhancement was assumed by Lithium lens.



Schematic layout of beamline used for tracking (ANL)

Liquid lead target:

$$X_0 \sim 0.5975 \text{ cm}$$


$$C = 162.9 - 3.022 \times 10^{-2} T + 8.341 \times 10^{-6} T^2 \text{ [J/(kg} \cdot \text{K)]}$$

$$K = 9.2 + 0.011 T \text{ [W/(m} \cdot \text{K)]}$$

$$\rho = 11367 - 1.1944 T \text{ [kg/m}^3\text{]}$$

Melting point: 600K , Boiling point: 2022K

At melting point, 1 J/cm³ can cause ~1.5K temperature change




AMD (6T) or
Lithium lens


Field map of 1.3GHz RF standing wave cavities. ~1.15m long,
surrounded by 0.5T solenoid, with ~12MV/m gradient

EM shower is simulated by EGS4.

Positron Yield



by W. Liu and W. Gai



NRC EGS4 by T. Kamitani

Positron yield $\eta(N_{e^+}/N_{e^-}/\text{GeV})$

► 0.6 GeV : 0.50
 ► 1.0 GeV : 0.45
 ► 2.0 GeV : 0.40

► 0.6 GeV : 0.44
 ► 1.0 GeV : 0.39
 ► 2.0 GeV : 0.37




Drive Energy (MK)

- ▶ The positron yield at the shower max for each energy is taken from the simulation.
- ▶ DR acceptance is smaller than AMD acceptance. The real yield is 87%, which corresponds to 1.5σ .
- ▶ No Enhancement by Lithium lens is assumed.
- ▶ The required drive beam intensity was obtained.

Ee- (GeV)	η	Ne- (nC)
0.7	0.27	11.85
1.4	0.48	6.67
2.2	0.71	4.51

ILC e⁺ source (MK)

- ▶ L-band RF gun (FLASH type) generates ILC format beam with 4.5nC bunch intensity.
- ▶ Three RF sections (2 klystron + 3 cryomodules, 24 cavities) accelerate it up to 2.2 GeV.
- ▶ Liquid lead target + Liquid Lithium lens.






Target vitality (MK)

- ▶ Operation is limited by BN isolation window.
 - ▶ **10×10^{12} GeV/mm² in 100ns duration**
 - ▶ **180kW average power**
- ▶ 2.2GeV, 4.5nC bunch with 369ns spacing, 2625 bunches, 5Hz
 - ▶ **3.1×10^9 GeV/mm² (spot size 20mm²)**
 - ▶ **$2.2 \times 4.5 \times 2625 \times 5 = 130\text{kW}$**
- ▶ Both limits are cleared. The average power would be half for LowP.
- ▶ The spot size can be smaller; The acceptance may be improved.
- ▶ Those limits should be confirmed by experiments.




Lithium lens, 700MeV, 3X₀ liquid Pb (ANL)




As showing in this figure, the maximum yield is about 0.46 when lithium lens is about 4cm thick and driven by 30KA current.

Comparing with yield of ~0.33 achieved by using AMD and immersed liquid lead target, using **lithium lens only** enhanced the capture by ~40%.

e+ Yield for different rms spot size of drive e- beam (ANL)



600MeV e- drive beam



700MeV e- drive beam



AMD is 6T to 0.5 T in 14 cm for all data points.

Lithium lens parameters are optimized for each case. We optimized both the thickness and the driving current density. The current is assumed to be uniform in the lens.

Increasing of the drive e- beam spot size will lower the yield enhancement from lithium lens.



Heat transfer simulation up to 130 bunches, 700MeV drive beam, 1mm spot size, AMD immersed target (ANL)



The difference between 700MeV and 600MeV drive e- is very small at this point.


Summary of the studies

Name	e- (GeV)	Spot (mm)	Pb flow (m/s)	Yield e+/e-	Ne- (nC)	NB limit
MK1	0.7	2.5	-	0.27	11.85	-
MK2	1.4	2.5	-	0.48	6.67	-
MK3	2.2	2.5	-	0.71	4.51	-
ANL1	0.7	1.0	10	0.45	7.11	182
ANL2	0.7	3.0	10	0.27	11.85	1200
ANL3	0.7	3.0	30	0.27	11.85	Saturated at 1973K
ANL4	0.7	4.0	30	0.27	11.85	Saturated at 1600K

- ▶ MK proposed 2.2 GeV drive beam.
- ▶ Boiling of Liquid Pb (2200K) is a serious problem according to ANL's study.
- ▶ High speed flow (20-30m/s) and larger spot size (2-3mm) help to avoid the boiling.

Total incident energy and deposit energy (ANL)

Assuming $3nC$ e^+ are captured



This figure from our previous conventional e^+ source study shows that lower drive beam energy will result in a higher energy deposition in target.

Energy deposition per captured e^+ does not have any strong dependence on the energy. It increases simply by X_0 .
(Comment by MK)

- ▶ The positron yield as a function of X_0 has an optimum point, but the dependence is not strong.
- ▶ On the other hand, the energy deposition per captured positron is simply increased as a function of X_0 .
- ▶ By considering both facts, another optimum is lower side of the extremum of the yield.

For 2.0 GeV drive beam

X_0	Yield (Ne+/Ne-/GeV)	Energy Deposit per e+ (J/3nC)
2	0.2	1.54
3	0.32	1.88
4	0.37	3
5	0.35	4.52

Optimization(2)

- ▶ Let me assumed 3 X_0 operation, rather than $4X_0$ for 2.2GeV drive beam.
- ▶ The positron yield (N_{e^+}/N_{e^-}) for 2.2GeV drive beam is $0.32 \times 2.2 = 0.70$.
- ▶ Taking account the DR acceptance and enhancement by lithium lens (30%), the yield becomes $0.70 \times 0.87 \times 1.3 = 0.80$.
- ▶ The drive beam intensity giving 3.2nC e^+ bunch is $3.2/0.8 = 4.0$ nC.

X_0	Yield ($N_{e^+}/N_{e^-}/\text{GeV}$)	Energy Deposit per e^+ (J/3nC)
2	0.2	1.54
3	0.32	1.88
4	0.37	3
5	0.35	4.52



Pb boiling extrapolation

- ▶ 2.2GeV, 4.0nC drive beam cause 1.65 J energy deposition per bunch.
- ▶ ANL's Pb boiling study was made with 2.30 J energy deposition per bunch.
- ▶ If the temperature rise is scaled as the energy deposition, the expected results are

Name	e- (GeV)	Spot (mm)	Pb flow (m/s)	Yield e+/e-	Ne- (nC)	NB limit
ANL1	2.2	1.0	10	0.80	4.00	250
ANL2	2.2	3.0	10	0.80	4.00	1670
ANL3	2.2	3.0	30	0.80	4.00	Saturated at 1590K
ANL4	2.2	4.0	30	0.80	4.00	Saturated at 1300K

Pb boiling extrapolation (2)

Name	e- (GeV)	Spot (mm)	Pb flow (m/s)	Yield e+/e-	Ne- (nC)	NB limit
MKV1	2.2	1.0	10	0.80	4.00	250
MKV2	2.2	3.0	10	0.80	4.00	1670
MKV3	2.2	3.0	30	0.80	4.00	Saturated at 1590K
MKV3	2.2	4.0	30	0.80	4.00	Saturated at 1300K

- ▶ MKV1: no way?
- ▶ MKV2: Acceptable for LowP set.
- ▶ MKV3, MKV4: Acceptable for Nominal set.



Summary

- ▶ Two independent studies on the e- driven positron source were compared.
- ▶ The positron yield calculations were consistent to each other.
- ▶ Yield enhancement by Lithium lens comparing to AMD was shown by ANL's study.
- ▶ MK's study shows 2.2 GeV drive beam is a solution, but no enhancement by LL is assumed.
- ▶ ANL's study shows that Pb boiling is a serious issue. Larger spot size and higher flow speed avoid the boiling.

Summary (cont.)

- ▶ Accounting both yield and energy deposition, low X_0 point is another optimum.
- ▶ By assuming 2.2GeV drive beam, 30 m/s flow speed is required to avoid the boiling.
- ▶ 10 m/s speed is acceptable for LowP set.