

Sources of Field Perturbations


LLRF Lecture Part 2

S. Simrock, Z. Geng

ITER / SLAC



RF System Architecture





Sources of Field Perturbations

o **Beam loading**

- Beam current fluctuations
- Pulsed beam transients
- Multipacting and field emission
- Excitation of HOMs
- Excitation of other passband modes
- Wake fields

o Cavity drive signal

- HV- Pulse flatness
- HV PS ripple
- Phase noise from master oscillator
- Timing signal jitter
- Mismatch in power distribution

o Cavity dynamics

- cavity filling
- settling time of field

o Cavity resonance frequency change

- thermal effects (power dependent)
- Microphonics
- Lorentz force detuning

o Other

- Response of feedback system
- Interlock trips
- Thermal drifts (electronics, power amplifiers, cables, power transmission system)



Lorenz Force Detuning



Cavity Deformation by Electromagnetic Field Pressure

Repulsive magnetic forces


Attractive electric

forces

Radiation pressure

$$P = \frac{\left(\mu_0 \left| \vec{H} \right|^2 - \varepsilon_0 \left| \vec{E} \right|^2\right)}{4}$$

Resonance frequency shift







Lorenz Force Detuning


- Effects of Lorenz force detuning
 - Change cavity voltage and phase during RF pulse
 - Generate more reflection power
 - Limit maximum repetition rate of RF pulses

Properties

- Gradient dependent
- Predictable from pulse to pulse
- Perturbations are correlated from cavity to cavity



Measurement of Lorentz Force Detuning



Frequency drift during 950 µs flat top (TESLA 9-cell cavity):

$$\Delta f_{FT} \approx -(0.4 \text{ to } 0.65) \frac{Hz}{MV/m^2} E_{acc}^2$$




Microphonics



Sources of Microphonics

 Mechanical vibrations caused by the accelerator environment are always present and may be transferred to the cavity.






Microphonics

- Effects of microphonics
 - It mainly influences the resonance frequency of the cavity and therefore the RF phase with respect to the beam
- **Properties**
 - Slow perturbation
 - Not predictable
 - Uncorrelated along the Linac




Microphonics at JLAB





Microphonics at FLASH



S. Simrock & Z. Geng, 7th International Accelerator School for Linear Colliders, India, 2012 12




Beam Current (Bunch Charge) Fluctuation




Beam Loading Effect

- Single bunch transient is not controllable
- Bunch charge fluctuation will introduce energy spread





Bunch Charge Pattern at FLASH






Phase Noise of Master Oscillator



Phase Noise of FLASH MO






Thermal Drift




Phase Drift of 80 m 7/8" Reference Line at FLASH





Error Map





Reference

[1] T. Schilcher. Vector Sum Control of Pulsed Accelerating Fields in Lorentz Force Detuned Superconducting Cavities. Ph.D. Thesis of DESY, 1998

[2] V. Ayvazyan, S. Simrock. Dynamic Lorenz Force Detuning Studies in TESLA Cavities. EPAC 2004, July 2004.