


Report on ScW-ECAL DESY beam test and future plans

17th December 2012

**K. Kotera,
Shinshu University**




Yesterday, I've taken this through the window of Azusa train when I moved from Shinshu to Tokyo.


Contents

1. ScECAL technological prototype and its purpose
2. test beam
 1. MIP response
 2. Shower response
 3. LED calibration
3. Problems
4. Summary and future.

Purpose of technological ScECAL




ScECAL physics prototype in front of the AHCAL at FNAL




Linearity:
deviation < 2%

Resolution:
Stochastic $12.9 \pm 0.4\%$
Constant $1.2^{+0.4}_{-1.2}\%$


Nice performance of
Physics prototype



Purpose of technological ScECAL



Electronics should be put in between sensor layers for ILD




this carton is not true because electronics should cover the sensor

Tungsten absorber 2-4 mm

Scintillator strips


Base board of Electronics and MPPC

Copper radiator



scintillator


MPPC





To Show how the technology works well

ScECAL technological prototype

- One layer one base board (EBU) prototype so far.
- Four SPIROC2b (ASIC) on an EBU controls 144 MPPCs.




The other side.





DIF, LED controller, and Power controller are the same technology as the AHCAL HBU

ScECAL technological prototype

- One layer one base board (EBU) prototype so far.
- Four SPIROC2b on an EBU controls 144 MPPCs.





The other side.




TB version DIF does not work with two EBU. We gave up to use two EBU.

MPPC-scintillator strip

- 36 MPPCs/row on a polyimide ribbon.
- The polyimide ribbon is for only mechanical support.





replaced




- A reflector ribbon with holes as MPPC windows is put in front of MPPCs
- Polyimide sheets are put on the EBU (only in front of MPPC).

Test beam at DESY with 1-6 GeV e^-





24th beam line

Address of channels




Sp2b1: Channels 91:108, 127:144
 Sp2b2: Channels 73:90, 109:126
 Sp2b3: Channels 19:36, 55:72
 Sp2b4: Channels 1:18, 37:54

Response to MIP events




Trigger threshold \ll 0.5 MIP



75% channels have succeeded to have good MIP distribution

: no signal or large noise

Response to MIP events



75% channels have succeeded to have good MIP distribution

: no signal or large noise

Shower events

Response of ScECAL behind

1. $0.7 X_0$ Tungsten absorber

2. $6.4 X_0$ Tungsten absorber


3 GeV e^- events

<10 cm
upstream of
ScECAL

$0.7 X_0 \times (1 - 14)$ layers


Mean of Energy deposit in each channel

event display




3 GeV e^- w/ $0.7 X_0$ absorber.

event display




3 GeV e^- w/ $6.4 X_0$ absorber .


Pedestal shift between LED mode and TB mode



Shift to lower side




3 GeV e^- w/ 6.4 X_0 absorber .



Using pedestal in TB mode, we can see the tail spread or the halo of beam




3 GeV e^- w/ 6.4 X_0 absorber .






ADC/MIP conversion factors

- Using pedestals taken in the test beam mode.
- 108 entries of available channels (75%).
- RMS/Means = 19.3%
(This is the same as in the case of FNAL physics prototype accidentally?)





Pseudo-Multilayer ScECAL

- Longitudinal shower profile is plotted.
- Shower maximum is reasonable 6-7.
- Some amount of offset comes from noise will be estimated.
- Zero absorber data will be added from the mip measurements.
- From the result of **physics** prototype tested at DESY(2007)





LED lights for gain monitoring



EBU has LEDs for each channel

LED lights for gain monitoring



 No space for LED

7 x 4 for ASICs.




2 x 2 for power connectors.

32 channels have no LED.

We need to ask to reduce the size of SPIROC package not only in thickness but also in area by using some package technique.

Next time, we can reduce the number of LED by sharing an LED with more than two channels





LED lights for gain monitoring



█ : no LED by ASIC or connector

- (#good channels)/(144-32) = 50%.
- There is no any good LED channel on ASIC132.

ASIC 132 LED on (but we can see normal pedestal with 0 V LED ► LED current makes noise?)



Summary


- 1. We have had the test beam experiment for the ScECAL 144 channel technological prototype using electron beam at DESY.**
- 2. We have seen the distribution of MIP energy deposit with MPV of around 7 p.e. for 75% of channels.**
- 3. The number of successful channels of gain monitor with LED system is 50% of channels which have LED light, so far.**
- 4. We recognize problems as in the following page...**

Problems we recognized



- 1. DIF cannot control multiple EBU for the TB mode so far.**
- 2. Individual threshold cannot be available so far.**
- 3. A SPIROC2b has 16 analog memory cells. This means that 16 events can be taken for a spill and the conversion factors between the analog memory cell and ADC has difference by memory cell by memory cell.**

Response changes depending on 16 memory cells

MIP distribution of ch.24 of SPIROC 130, 131 every memory cells together



The p.e. peaks are smeared for most of other channels



One memory cell.

We can clearly see the p.e. peaks.

Problems we recognized

1. DIF cannot control multiple EBU for the TB mode so far.
2. Individual threshold cannot be available so far.
3. A SPIROC2b has 16 analog memory cells. This means that 16 events can be taken for a spill and the conversion factors between the analog memory cell and ADC has difference by memory cell by memory cell.
4. Some events have a triggered channel which has small ADC counts than the true one.
5. Many unavailable LED channels.
6. LED system makes strange noise on #132.
7. We need more photon yields.
8. . . .

Future plan

1. Near Future:

1. Two layer (x and y type) ScECAL prototype,
2. Combined with Si-W-ECAL prototype (Hybrid ECAL),

2. Further more,

1. Fix the technology and design of Scintillator-MPPC unit,
2. more compactification of electronics.

1. ASIC,


2. Central detector interface.

back up


Plan of the analyses

1. Precise analysis of MIP and pedestal.
2. Precise analysis of gain with LED run data.
3. Study on the fluctuation of memory cells by measuring LED p.e.-ADC depending on memory cells (data has a flag).
4. Study on LED system using EBU at Shinshu [We have brought two EBUs including one full equipped EBU, central interface board (DIF, LED, Power)] and its frame.
5. TDC analysis (we have data)
6. Power pulse study in our lab in shinshu and in the next TB.
7. More EBUs, more layers, and Hybrid ECAL.


Response to MIP events



We checked MPPC-Window matching




window/MPPC matchings were good



75% channels have succeeded to have good MIP distribution


Nevertheless we removed the reflector ribbon and 2nd row came back!

SPIROC2b logic for auto trigger mode




Issues should be optimized

- Shaping time (like gate length, ASIC by ASIC)
 - we tuned to 100 ns
- Delay time (ASIC by ASIC)
- Spill signal delay
- Bias voltage (channel by channel)
- Threshold for auto trigger
 - global (ASIC by ASIC) : we used
 - channel by channel : not available so far,
- Preamplifier (channel by channel)
 - maximum value in this TB
 - in future, tune this value to have 0.5 MIP threshold at the same DAC value for all channels.




Logics



MPPC-scintillator strip

- 36 MPPCs/row on a polyimide ribbon.
- The polyimide ribbon is for only mechanical support.



Purpose of technological ScECAL

- To check feasibility of one layer unit and its control unit.
[To check if we can control two ECAL base board unit (EBU) from one control unit.]
- Detail test issues:
 1. Performance on energy measurement.
 1. Verification of MIP measurement ability.
 1. stability of procedure,
 - scintillator-MPPC-amplifier-charge-ADC
 2. separation from noise
 2. Gain measurement with builtin LED system.
 2. Other functions.
 1. TDC,
 2. power pulsing system next TB...

Purpose of technological ScECAL




- To check feasibility of one layer unit and its control unit.
[To check if we can control two ECAL base board unit (EBU) from one control unit.]
- Detail test issues:
 1. Performance on energy measurement.
 1. Verification of MIP measurement ability.
 1. stability of procedure,
 - scintillator-MPPC-amplifier-charge-ADC
 2. separation from noise
 2. Gain measurement with builtin LED system.
 2. Other functions.
 1. TDC,
 2. power pulsing system next TB...

Done: some tunings

9. Others

1. large statistics of:

1. MIP measurement with 0.5 MIP threshold
2. delay time for TB run and LED run
3. DAC-ADC relation



Purpose

1. System test in lab (2.5 weeks).
 - ADC, TDC, auto trigger, power pulsing
 2. LED calibration in lab. including noise monitoring (0.5 weeks)
-
3. installation (0.5 week)
 4. noise run (2 days)
 5. LED calibration (2 days)
 6. 3 GeV electron run w/o absorber (2 days)
 7. electron run w/ absorbers (0.5 week)
 - one absorber, two absorbers, three absorbers, ...
 - x 1 GeV, 3 GeV, 6 GeV
 8. withdraw
- in laboratory
- on beam line
-